

2-WAY SPEAKER

ERA 12

12" 2-WAY PASSIVE SPEAKER

DESCRIPTION

ERA 12 is a multipurpose two-way full-range professional speaker system, suitable for a wide range of applications, such as live sound reinforcement and stage monitoring as well as distributed sound systems for clubs or music venues.



WOOFER



Max SPL



TWEETER



Max POWER



FEATURES

- Power-800W Max.
- 97dB max SPL
- 70Hz-16kHz Frequency Response
- 12" Woofers, 2.5" VC
- 1" Tweeter, 1.35" VC

KlA^{ng}meister



ERA 12

DATASHEET

Technical Specifications

Electronic specifications	Frequency Response (-10dB):	70 Hz ÷ 16 kHz
	Max SPL@1m:	126dB
	Horizontal Coverage Angle:	90°
	Vertical Coverage Angle:	60°
	System Sensivity:	97dB
Audio Power	Amplification:	Full Range
	AES:	400W
	Program:	800W
	Nominal Impedance:	8Ω
	Crossover Frequency:	2050Hz
	Recommended Amplifier:	KX3000, KX4000
Transducers	Woofers:	12", 2.5" Voice Coil
	Tweeter:	1", 1.35" Voice Coil
Input/Output Section	Input Connector:	Speakon-NL4
	Output Connection:	Speakon-NL4
Standard compliance	Safety agency:	CE compliant
Physical Specifications	Cabinet/Case Material:	PP
	Handles:	2
	Grill:	Metal
	Color:	Black
Package Dimensions	Height:	67.5cm
	Width:	43cm
	Depth:	40cm