

2-WAY SPEAKER

NEO 10A

10" 2-WAY ACTIVE SPEAKER

DESCRIPTION

NEO 10 is a multipurpose two-way full-range professional speaker system, suitable for a wide range of applications, such as live sound reinforcement and stage monitoring as well as distributed sound systems for clubs or music venues.



WOOFER



Max SPL



TWEETER



Max POWER



FEATURES

- Power-400W Max.
- 125dB Max. SPL
- 80Hz-16kHz Frequency Response
- 10" Woofers, 2.0" VC
- 1" Tweeter, 1.35" VC

Klangmeister



NEO 10A

DATASHEET

Technical Specifications

Electronic specifications	Frequency Response (-10dB):	80 Hz ÷ 16 kHz
	Max SPL@1m:	125dB
	Horizontal Coverage Angle:	90° Elliptical
	Vertical Coverage Angle:	90° Elliptical
Power Sections	Amplification:	Full Range
	AES:	150W+150W
	Program:	400W
	Cooling:	Air
	Connections:	VDE
Transducers	Woofers:	10", 2.0" Voice Coil
	Tweeters:	1", 1.35" Voice Coil
Processor Section	Crossover Frequencies:	2100 Hz
	Protection:	Thermal, Overload, Short circuit
	Limiter:	Soft Limiter
	Audio Control:	Volume
	AC Mode:	Music-Flat / Mic/Line
Input/Output Section	Input Connector:	XLR Female
	Input Signal:	Balanced/Unbalanced
	Input Sensitivity:	-2 dBu/+4 dBu
	Output Connectors:	XLR Male
	Output Signal:	Balanced/Unbalanced
	Power Connectors:	IEC Male
	Main Power:	AC 180-250V - 50 Hz
Indicators:		Power, Limiter
Standard compliance	Safety agency:	CE compliant
Physical Specifications	Cabinet/Case Material:	PP
	Handles:	2
	Grill:	Metal
	Color:	Black
Package Dimensions	Height:	46.5cm
	Width:	30cm
	Depth:	28.5cm